

					TABLA DE ENROLLAMIENTO MÁXIMO							
					CAJONES							
					ALUMINIO PERFILADO				CAJONES PVC			
									STANDARD			
LAMAS		CAJÓN	ANCHO MÁXIMO ACONSEJADO	EJE	137	165	180	205	155	185	200	225
ALUMINIO TERMICO		Micralum 39	2,00	40	1,60	2,55	3,00	4,10	1,85	2,85	3,35	4,55
				60	1,45	2,30	2,85	3,85	1,65	2,80	3,25	4,35
		Minicur 43	2,20	40	1,35	2,25	2,80	3,85	1,65	2,75	3,20	4,20
				60	1,30	2,10	2,65	3,70	1,55	2,70	3,10	4,00
		Termilum 45	2,00	40	1,55	2,60	3,05	4,00	1,70	2,90	3,40	4,25
				60	1,40	2,45	2,80	3,85	1,55	2,45	3,20	4,15
		Termicur 45	3,00	40	1,35	2,15	2,65	3,55	1,55	2,55	2,65	3,60
				60	1,30	2,10	2,55	3,40	1,35	2,35	2,45	3,55
		Termicur 50	3,75	60	0,95	1,50	1,90	2,80	1,05	1,95	2,15	2,80
SEGURIDAD		Mini-Segur 40	3,00	60	0,90	1,70	2,15	2,70	1,10	1,75	2,20	3,15
		Autoblocante 39	3,00	60	1,15	2,00	2,35	3,15	1,45	2,30	2,60	3,30
		Autoblocante 45	3,50	60	0,85	1,35	1,85	2,60	1,25	1,70	2,05	2,80
PVC		P-37	1,50	40	0,90	2,15	2,80	3,20	1,60	2,45	2,85	3,95
*MEDIDAS TOTALES INCLUIDO EL CAJÓN												